



Model	PFW160-2C	PFW200-2C	PFW160-4C	PFW200-4C	PFW250-4C
Welding Range(mm)	(40 50) 63 75 90 110 125 140 160	(40 50) 63 75 90 110 125 140 160 180 200	(40 50) 63 75 90 110 125 140 160	(40 50) 63 75 90 110 125 140 160 180 200	(50 63 75) 90 110 125 140 160 180 200 225 250
Heating Plate Max. Temperature	270℃	270℃	270℃	270℃	270℃
Temperature Deviation in Surface	≤±5℃	≤±5℃	≤±5℃	≤±5℃	≤±5℃
Working Voltage, Frequency	220V,50/60Hz	220V,50/60Hz	220V,50/60Hz	220V,50/60Hz	220V,50/60Hz
Total Power	1.71KW	2.31KW	1.71KW	2.31KW	2.83KW
Heating Plate Power	1.0KW	1.6KW	1.0KW	1.6KW	2.0KW
Planning Tool Power	0.71KW	0.71KW	0.71KW	0.71KW	0.83KW
Weight	40KG	50KG	60KG	90KG	130KG
Package	1 Wooden Box	1 Wooden Box	1 Wooden Box	1 Wooden Box	1 Wooden Box
Volume	0.15CBM	0.15CBM	0.18CBM	0.18CBM	0.3CBM